




Sealtite Type NMFG (Type B): Food Grade Non-metallic Flexible Conduit


NMFG:



Co-extruded spiral with smooth inner and outer walls

Trade	Item	Std. Pkg.	Inside Diameter	Outside Diameter		Bend	Weight
Size	ID	M / FT	Min	Min	Max	Diameter	Kg/m (lbs/cft)
3/8" (12)	359.012.0	30 / 100	12.29 (0.484)	17.53 (0.690)	18.03 (0.710)	102 (4.0)	0.17 (11)
1/2" (16)	359.016.0	30 / 100	15.80 (0.622)	20.83 (0.820)	21.34 (0.840)	165 (6.5)	0.23 (15)
3/4" (21)	359.020.0	30 / 100	20.83 (0.820)	26.16 (1.030)	26.67 (1.050)	216 (8.5)	0.30 (20)
1" (27)	359.026.0	30 / 100	26.44 (1.041)	32.77 (1.290)	33.40 (1.315)	330 (13.0)	0.40 (27)
1-1/4" (35)	359.035.0	15 / 50	35.05 (1.380)	41.40 (1.630)	42.16 (1.660)	406 (16.0)	0.53 (36)
1-1/2" (41)	359.040.0	15 / 50	40.01 (1.575)	47.37 (1.865)	48.26 (1.900)	457 (18.0)	0.67 (45)
2" (53)	359.050.0	15 / 50	51.31 (2.020)	59.44 (2.340)	60.33 (2.375)	564 (22.2)	1.00 (67)

All dimensions in mm (inches)



Sealtite Type NMFG :

RoHS



- Food Grade Non-metallic Type B liquid-tight conduit.
- Designed for Food Processing applications.
- NSF Certified to NSF/ANSI 169 for special purpose food equipment or devices.
- Delivers superior wiring protection where incidental food contact is possible.
- Jacket easily cleaned and does not promote bacteria growth.
- Uses special non-metallic connectors for easy installation. Can also be used with standard liquid-tight connector.
- Available in custom cut lengths

SPECIFICATIONS:

- Co-extruded PVC conduit.
- PVC formulated for food applications per FDA CFR 21 and NSF 169 Requirements
- Colour: Blue (RAL 5015)
- Temp. range: -35°C to +60° C (-31°F to +122°F)

APPLICATIONS:

- Food processing facilities
- Restaurants
- Poultry packing facilities
- Meat packing facilities
- Wash down areas
- Waste water treatment
- Pharmaceutical applications
- Special purpose food equipment or devices